

MATERIAL SAFETY DATA SHEET

WOOD STAIN GOLDEN

Page:

PRODUCT NAME: WOOD STAIN GOLDEN

HMIS CODES: H F

PRODUCT CODE: WS-665

1 2

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: LANCO MFG. CORP.

DRESS : URB. APONTE #5
SAN LORENZO, PUERTO RICO
00754

EMERGENCY PHONE : (787) 736-4200

DATE PRINTED : 08/11/00

FORMATION PHONE : (787) 736-4200

NAME OF PREPARER : VICTOR M. HERNANDEZ

SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

TABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mm Hg @ TEMP	WEIGHT PERCENT
IPANOL ACGIH TLV: 400 PPM, OTHER: 500 PPM	67-63-0	33	68 F
MATIC SOLVENT OSHA PEL: 500 PPM, ACGIH TLV: 100 PPM, OTHER: N/A	64742-88-7	2	68
ACONITUM 24%	125328-521	10	25 C
BALTO 12%	MIXTURE	1	77
OSHA PEL: 500 PPM, ACGIH TLV: 100 PPM, OTHER: N/A			

Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.
Information available.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling RANGE: 180 deg F - 380 deg F

SPECIFIC GRAVITY (H2O=1): 0.81

OR DENSITY: HEAVIER THAN AIR

EVAPORATION RATE: SLOWER THAN ETHER

Boiling V.O.C.: 5.58 lb/gal

MATERIAL V.O.C.: 4.98 lb/gal

SOLUBILITY IN WATER: NON SOLUBLE

APPEARANCE AND ODOR: SOLVENT ODOR

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash POINT: 53 deg F

METHOD USED: TCC

Flammable LIMITS IN AIR BY VOLUME- LOWER: .9

UPPER: 14.4

Extinguishing MEDIA: FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES

Protective EQUIPMENT SHOULD BE WORN TO AVOID INHALATION OF CONCENTRATED VAPOR. WATER SHOULD NOT BE USED EXCEPT AS FOG TO KEEP NEARBY SURFACES COOL.

ADDITIONAL FIRE AND EXPLOSION HAZARDS

Highly FLAMMABLE. VAPORS MAY IGNITE EXPLOSIVELY AND/OR CAUSE FLASH FIRES. ELIMINATE SOURCES OF IGNITION. NO SMOKING. USE ADEQUATE VENTILATION SUFFICIENT TO REMOVE ODOR OF SOLVENT AND VAPORS.

SECTION V - REACTIVITY DATA

Stability: STABLE

Conditions TO AVOID

Excessive HEAT, POOR VENTILATION, CORROSIVE ATMOSPHERES, EXCESSIVE AGING.

INCOMPATIBILITY (MATERIALS TO AVOID)

Oxidizing AGENTS, STRONG ACIDS AND OXIDIZING MATERIALS, ALKALINE MATERIALS.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS
ON MONOXIDE, CARBON DIOXIDE, AND OXIDES OF NITROGEN.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

SIGNS OF OVEREXPOSURE COULD BE HEADACHE, DIZZINESS, NAUSEA, UPPER RESPIRATORY DRYNESS OR IRRITATION, DROWSINESS, MENTAL DEPRESSION, AND ANAESTHESIA.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

CONTACT: SEVERE IRRITATION, TEARING, REDNESS AND BLURRED VISION.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

CONTACT: CAN DRY AND DEFAAT SKIN CAUSING CRACKS, IRRITATION, AND DERMATITIS.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

INGESTION: CAN CAUSE GASTROINTESTINAL IRRITATION, VOMITING, NAUSEA, AND DIARRHEA.

HEALTH HAZARDS (ACUTE AND CHRONIC)

INHALATION-DIZZINESS, BREATHING DIFFICULTY, HEADACHES, & LOSS OF COORDINATION. EYE CONTACT-SEVERE IRRITATION, TEARING, REDNESS, AND BLURRED VISION. SKIN CONTACT- CAN DRY AND DEFAAT SKIN CAUSING CRACKS, IRRITATION AND DERMATITIS. INGESTION-CAN CAUSE GASTROINTESTINAL IRRITATION, VOMITING, NAUSEA, & DIARRHEA. NO CHRONIC HEALTH EFFECTS.

MUTAGENICITY: NTP CARCINOGEN: No **IARC MONOGRAPHS:** No **OSHA REGULATED:**

ADDITIONAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

ASTHMA, RESPIRATORY TRACT IRRITATION, DERMATITIS, NAUSEA, VOMITING.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION OVEREXPOSURE - MOVE PERSON TO FRESH AIR. IF BREATHING STOPS, APPLY ARTIFICIAL RESPIRATION AND SEEK IMMEDIATE MEDICAL ATTENTION. EYE CONTACT- FLUSH WITH LARGE QUANTITIES OF WATER FOR 15 MINUTES. SKIN CONTACT- WASH THOROUGHLY WITH SOAP AND WATER AND GENTLY DRY. INGESTION DO NOT INDUCE VOMITING, CAN CAUSE CHEMICAL PNEUMONITIS AND PULMONARY EDEMA. CONTACT PHYSICAL IMMEDIATELY.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

ISOLATE IGNITION SOURCES, PROVIDE GOOD VENTILATION, DIKE SPILL AREA AND ADD ABSORBENT EARTH OR SAND/STYRENE DUST TO SPILLED LIQUID. THOROUGHLY MIX AND DISPOSE.

WASTE DISPOSAL METHOD

ABSORBENT/ WATER/ SPILLED LIQUID MIXTURE INTO METAL CONTAINERS AND ADD ENOUGH WATER TO COVER. CONSULT LOCAL, STATE & FEDERAL WASTE REGULATION BEFORE DISPOSING INTO APPROVED HAZARDOUS WASTE LANDFILLS. OBEY RELEVANT LAW.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

CONTAINERS CLOSED WHEN NOT IN USE. STORE 60-95 F OUT OF SUN. USE ADEQUATE VENTILATION TO AVOID BREATHING VAPOR WHEN COVERED. KEEP AWAY EXCESSIVE HEAT AND OPEN FLAMES.

OTHER PRECAUTIONS

USE PROTECTIVE EQUIPMENT WHEN HANDLING FLAMMABLE SOLVENT BORNE MATERIALS. SMOKING IN AREA WHERE THIS MATERIAL IS USED SHOULD BE STRICTLY PROHIBITED.

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION

WHEN HANDLING THIS MATERIAL USE A NIOSH APPROVED CARTRIDGE RESPIRATOR OR GAS MASK SUITABLE TO KEEP AIRBORNE MISTS AND VAPORS OUT OF THE BREATH.

CONCENTRATIONS BELOW THE TIME WEIGHTED THRESHOLD LIMIT VALUES. WHEN USING IN POORLY VENTILATED AND CONFINED SPACES, USE A FRESH-AIR
SUPPLYING RESPIRATOR OR A SELF-CONTAINED BREATHING APPARATUS.

VENTILATION

EFFICIENT TO KEEP WORKROOM CONCENTRATION BELOW TLV. VENTILATION EQUIP. MUST BE EXPLOSION PROOF.

PROTECTIVE GLOVES

CHEMICALS RESISTANT GLOVES.

EYE PROTECTION

CHEMICAL SAFETY GLASSES, GOGGLES, AND FACESHIELDS FOR EYE PROTECTION.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

IMPERMEABLE APRONS AND PROTECTIVE CLOTHING WHENEVER POSSIBLE TO PREVENT SKIN CONTACT. THE USE OF HEAD CAPS WHENEVER POSSIBLE IS
HIGHLY RECOMMENDED.

WASH/HYGIENIC PRACTICES

WASHES AND SAFETY SHOWERS IN THE WORKPLACE IS RECOMMENDED.

SECTION IX - DISCLAIMER

Information contained herein is based on data believed by this company to be accurate, but we do not assume any liability for
inaccuracy. We neither suggest nor guarantee that any hazards mentioned are the only ones which exist. The manner of that use and
whether there is any infringement of patents is the sole responsibility of the user.